



Technical Data:
142 SOLVENT 66
 Aliphatic Hydrocarbon

Box 2219, Columbus, Ohio 43216 - (614) 780-3333

142 SOLVENT 66, Aliphatic Hydrocarbon

	<u>SPECIFICATIONS</u>	<u>TYPICALS*</u>
Gravity, API at 60°F (D-287) (D-4052)		41.0 - 54.0
Specific Gravity at 60°F (D-4052) (D-287)	0.763 - 0.820	
Color (D-156)	+28 min	+30
Kauri-Butanol Test (D-1133)		31
Flash Point, °F, T.C.C. (D-56)	142 min	
Corrosion (D-130)	2 max	
Composition, Volume % Aromatics	1.0 max	
Distillation, °F (D-86)		
IBP	350 min (176.6°C)	
Dry Point	415 max (212.8°C)	

ASHLAND® 142 Solvent 66 meets the following specifications:
 MIL-PRF-680 (formerly P-D-680), Type II, Degreasing Solvent
 TT-T-291F, Type II, Thinner, High-Flash
 ASTM D-235, Type II
 A-A-2904, Type II, High-Flash Mineral Spirits

Code: 20594 (BULK)

*Typical values should not be construed as a guaranteed analysis of any specific lot.

() Indicates ASTM Test Method

© Copyright 2009, Ashland Inc.

® Registered trademark, Ashland Inc.

0811

NOTICE: Ashland makes no warranty or representation as to the suitability of the product as specified herein for any particular application. The determination of the suitability of the above specification for any particular use is solely the responsibility of the user.

All precautionary labels and notices should be read and understood by all supervisory personnel and employees before using. Consult Ashland Distribution Company and OSHA regulations for additional safety and health information. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product. Special attention should be given to consumer applications. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.