

JACK FROST PERMANENT COOLANT/ANTIFREEZE (GREEN)

Product Specification Sheet

FEATURES:

- Protection of cooling system metals from corrosion
- Protects aluminum from corrosion
- Protection against winter freeze-up or summer boil over
- Uniform heat transfer
- Non-foaming
- Safe on rubber hoses, water pumps, gaskets or exterior finishes
- Can be mixed with other brands of antifreeze

Meets or Exceeds:

GM1899M

GM1825M

ASTM3306

ASTM4985 (Cummins Service Bulletin 85T-2 and SAE J1034)

Recommended for use in:

Can be used in both passenger cars and heavy-duty vehicles.

TYPICAL CHARACTERISTICS:

Freezing Protection

50% Antifreeze Solution °F -34

Specific Gravity 60/60 F 1.13

Flash Point, °F, Min. 250

Color Green

Equilibrium Boiling Point. °F 325 Min.

Foam (ASTM D1881

Milliliters Increase 50 Max.

Seconds, Break Time 5 Max.

Reserve Alkalinity 10 Max.

Water, % 5 Max.

ph: Concentrate 10.0-10.9

33.3% Antifreeze Solution 10.0-10.5

Antifreeze Glycols, % 95 Min.

Anhydrous Alkali Metasilicate 0.09%

AVAILABILITY

6 X 1 Gallon Cases

55 Gallon Drums Concentrate

55 Gallon Drums 50/50 Pre-Diluted

Revised October 2012